




**CERTIFICATION & SUBMITTAL
MODEL 8160 ROOF CURBS
SELF FLASHING STYLE**



STANDARD SPECIFICATIONS

- **SHELL & BASE PLATE:** 18 ga. galvanized press formed steel. Continuous welds on shell seams, including all corners on 4" flanges.
- **INSULATION:** 3 LB. per cu.ft.density, rigid fiberglass.
- **WOOD NAILER:** None.
- **AVAILABLE "T" DIMENSIONS:** MODEL 8161: 1-1/2" - standard
MODEL 8163: 3-1/2"
MODEL 8165: 5-1/2"

OPTIONS

- 55 Neoprene gasket 1 1/2" or 2" x 1/4" (please specify)
- 60 18 ga. galvanized liner
- 61 .063 Aluminum liner
- 62 Damper holding base
- 63 Burglar Bars 1/2" diameter
- 65 One way pitch
- 66 Two way pitch
- 71 Pipe curb assembly (accommodates 2 pipes 3/8" thru 1" and 2 pipes 1" thru 2")
- 72 Pipe curb assembly (accommodates single pipe 2" thru 6")
- 81 16 ga. construction
- 82 14 ga. construction
- 86 Aluminum construction
- WN Wood nailer, factory installed

NOTES

1. MINIMUM RECOMMENDED "H" = 8"
2. Large units, depending on freight requirements are shipped knocked down in multiple sections for field assembly.

